

ERBESSD INSTRUMENTS®

EI SERIES

Balancing Machines

EI-6000

The ideal balancing machine for all types of rotating parts up to 6000kg including rollers, motor rotors, crankshafts, mills, and many others.



The floating bases of the EI-6000 are manufactured **tough** and **light** to reduce mechanical inertia.

TECHNICAL SPECIFICATIONS


Dimensions: 3000 x 1750 x 1325 mm	Sequential unbalance reduction: 95%	Weight: 520 kg (1146lb)
Max rotor diameter: 1800 mm (71 in)	Max weight per base: 3000 kg (6613 lb)	Power transmission: Flat belt
Max journal diameter: 343 mm (11 in)	Max SBS displacement: 38 mm (3.1 in)	Lubrication: Manual
Precision: ±0.01 mm/s	Accelerometer Sensitivity: 100 mV/g	Residual unbalance: 2 gr·mm/ 100kg rotor
Min/Max symmetric load: 150 kg (330 lb) 3000 kg (6613 lb)	Min/Max distance between supports: 500 mm (7.8 in) -- mm (-- in)	Motor features: 7.4 kW (11 HP) 220 / 440 V, 3 phases, 4 poles
	Speed driver (VFD): Included	

For more information. Visit our **YouTube** page.

<https://www.youtube.com/c/ErbessdinstrumentsOfficial>

Every balancing machine in the **EI Series** has a **Soft Bearing Suspension (SBS)** built in.


The **SBS** technology guarantees the most reliable balancing with the easiest to use software.



The **SBS** base has the capability to rotate itself within its axis and has an **horizontal 45° tilt**. These features protect the poles and provide maximum **durability**.





ADAPTABILITY LIKE NO OTHER




The EI 6000 **pedestals can be adjusted** to adapt to a wide variety of shafts.

The **height** of the base **can also be changed** to fit rotors with different diameters.



And the **transmission adjuster** will help you achieve the perfect height and tension between the bench and your rotor.

INCLUDED DEVICES



DigivibeMX

Balancing software for 1 and 2 planes
 Calculator with 12 functions
 Balancing Wizard & in situ
 Quality grade
 Polar graphics with vibration phase



Accelerometers AC500 (2)

Sensitivity: 100mV/G
 Frequency response: 0.32-10 KHz
 Magnetic base included
 Made of stainless steel
 Standard 3 pin MIL connector



Laser optical sensor

Analogic output
 Range 1-5,000 Hz
 Operation distance: 20 cm to 15 cm
 Nylamid body
 Magnetic base and cables included



GX400

Up to 4 monoaxial accelerometers or 1 triaxial and 1 monoaxial accelerometers
 Cables included
 Compatible with 5V sensors
 Sample rate: 48,000 Hz
 Frequency range: 0.5 - 20,000 Hz
 Use it for dynamic balancing and vibration analysis

The **EI-6000** also includes one of the most powerful **motors** in the market and a high quality **speed driver**.

ADDITIONAL ACCESORIES

Negative load support



Accessory required to secure rotors with high vibration levels like crankshafts. Ensures your balancing is more **secure** and **precise**.

Tablet Windows Surface

One of the most powerful Windows tablets.

The perfect device for dynamic balancing using **DigivibeMX**.



ERBESSD INSTRUMENTS®

WORLDWIDE toll-free:

+1-877-223-4606

ENGLISH:

Sales, Service & Support Engineer

+1-518-874-2700

info@erbessdreliability.com

SPANISH & FRENCH:

Sales, Service & Support Engineer

+52 (55) 6280-7654

info@erbessd-instruments.com

BUY ONLINE

www.erbessd-instruments.com

ALL THE IMAGES ARE FOR ILLUSTRATIVE PURPOSES ONLY. THE FINAL PRODUCT MAY VARY DEPENDING ON THE VERSION AND/OR THE CHANGES OR UPGRADES MADE TO THE PARTS AND COMPONENTS OF THE DEVICES

© 2018 ERBESSD INSTRUMENTS

EI6K-DS2021.0724.15