

ERBESSD INSTRUMENTS®

PHANTOM

Vibration Sensor

PHANTOM Gen 2, the best wireless condition monitoring system worldwide with **the best battery in the market.**



The triaxial vibration sensor is able to send **3 simultaneous** FFT and Time waveform recordings at once.

Phantom Gen 2 has most of the same features as the Phantom Expert but with less space!

TECHNICAL SPECIFICATIONS

You can find **Phantom Gen 2** in it's **High Sensitivity** version (EPH-V17) or in it's **High Range** version (EPH-V18).
Just as the **Phantom Expert**.

MEASUREMENT						
Part Number: EPH-V17	Sensor: MEMS triaxial accelerometer					Dynamic Range: 2G / 4G / 8G
Frequency Range: 4 kHz (x,y) 1.8 kHz (z)	Spectral Noise: 130 µg/√Hz					Data Receiving Interval: 6 hours (min) / Configurable
Recording Time(s):	1	2	4	8	16	Resolution Lines: 6400
Sample Rate (Hz):	25600	12800	6400	3200	1600	Sensitivity: 100mV/G
Max Frequency (Hz):	4000	2000	1000	500	250	
MEASUREMENT						
Part Number: EPH-V18	Sensor: MEMS triaxial accelerometer					Dynamic Range: 8G / 16G / 32G
Frequency Range: 10 kHz (x,y) 5.1 kHz (z)	Spectral Noise: 630 µg/√Hz					Data Receiving Interval: 6 hours (min) / Configurable
Recording Time (s):	1	2	4	8	16	Resolution Lines: 6400
Sample Rate (Hz):	25600	12800	6400	3200	1600	Sensitivity: 100mV/G
Max Frequency (Hz):	10000	5000	2500	1250	625	

POWER SUPPLY

Battery Lifetime:

12,000 measurements
Standby mode if Gateway not detected

Main Power Supply:

Lithium battery CR2032 3V
(Replaceable)

CONNECTIVITY AND SOFTWARE

Wireless Protocol:

Bluetooth BLE 5.0 / Modbus via Gateway

Signal Strength Range:

-90dBm to -30dBm

Power Output Range:

-4dBm to +8dBm
(Configurable)

Software Compatibility:

DigivibeMX Phantom Version
/ WiSER Vibe
Firmware Updates via
Phantom Manager (iOS & Android)

Wireless Range:

100m line sight

Operating Frequency:

2.4GHz

DIMENSIONS

Dimensions:

37.7mm x 33.7mm

Weight:

117 gr

Base Temperature Range:

-7 to 60 °C
(20 to 140 °F)

Material:

ABS / Stainless Steel

Protection Rating:

Water and dust resistant (IP67)

Analyze and visualize the data of your sensors with

DigivibeMX®

Access to your information in an easy way trough your browser or with DigivibeMX.



Phantom sensors are compatible with communication protocol



QUICK GUIDE

Place your sensor the right way!



Use the symbol on the top of the Phantom to locate the axis in the right position.



Once that you've placed the sensor on your machine, set it up on Digivibe and define each axis to an orientation: Horizontal, Vertical and Axial.

ACCESORIES

The Phantom vibration sensor has everything you need to start collecting data without the need of additional accessories.

Add it to your measurement point trough DigivibeMX and you will be ready to monitor your machines.



It's smart design allows you to place it anywhere you want using the right tools.

Just worry about where to place the sensor. We have the magnetic base perfect for the job.

MEET THE PHANTOM FAMILY

Phantom RPM

With the RPM sensor you can easily analyze the revolutions per minute of any rotor, turbine or vent with incredible precision with a switching speed of 600kRPM.



Phantom Termocouple & Phantom Infrared

Have a better control of your machines' temperature. You can connect up to 3 thermocouple sensors or acquire the infrared temperature sensor so you can monitor with extreme precision.



Phantom Current

The Phantom current module allows you to measure up to 4 amperage channels with clamps that start with 50 amp and go to 500 amp.



Phantom GP

General Purpose modules that are compatible with any kind of sensor to obtain wireless data. Available for 4-20mA, 0-10V, Digital Signals and 2.2Vpp sensors.



Phantom All in One

Obtain the reliability of three sensors in only one Phantom module; vibration, temperature and current. Complete condition monitoring all in one.



Coming soon...

Phantom
Thermographic
Camera



ERBESSD INSTRUMENTS®

WORLDWIDE toll-free:

+1-877-223-4606

ENGLISH:

Sales, Service & Support Engineer

+1-518-874-2700

info@erbessdreliability.com

SPANISH & FRENCH:

Sales, Service & Support Engineer

+52 (55) 6280-7654

info@erbessd-instruments.com

BUY ONLINE

www.erbessd-instruments.com

ALL THE IMAGES ARE FOR ILLUSTRATIVE PURPOSES ONLY. THE FINAL PRODUCT MAY VARY DEPENDING ON THE VERSION AND/OR THE CHANGES OR UPGRADES MADE TO THE PARTS AND COMPONENTS OF THE DEVICES

© 2018 **ERBESSD INSTRUMENTS**