

Universal ICP Accelerometer
Wireless Adapter

# GP8

# Universal ICP Accelerometer Wireless Adapter

GP8 is the only 8-Channel Universal ICP Accelerometer to Wireless Phantom converter with Modbus communication for additional standard applications.



#### **Main Characteristics:**

Full waveform and spectrum data.

**BLE 5.0** communication.

**Modbus** protocol added.

**31 kHz** Sample Rate.

**6400 líneas** de resolución.

Velocity RMS Values **every 5 minutes.**Internal Velocity RMS calculated **every 30** 

**seconds** for alarm settings

8 Simultaneous Measurement Points.


With the 8 embedded BNC connectors, you can connect any of your standard ICP accelerometers and add them to your **Phantom** continuous monitoring system.





GP8 Can work with 5VDC power supply. Additionaly, GP8 works with Phantom Standar Gateway receiver, supporting more than 100 sensor at the same time.

The data collection interval is configurable so this way you can keep track of all your measurements constantly.






Compatible with your most reliable Erbessd Instruments software such as **DigivibeMX** and **WiSER Wibe**.

# DIMENSIONS & SPECIFICATIONS





#### **MEASUREMENT**

Max AC Input 2.5 Vpp
Power Supply 5VDC / 1 A
Sample Rate 31250 Hz
Channels 8 Channels
Internal Temperature Accuracy  $\pm$  5 °C ( $\pm$  41°F)
Status (every 5 minutes) Temperature and RMS
Data Interval 10 minutes (configurable)

#### **CONNECTIVITY AND SOFTWARE**

Wireless Protocol Bluetooth BLE 5.0

Modbus via Gateway


Operating Frecuency 2.4 GHz
Wireless Range 100m Line Sight
Software DigivibeMX (Phantom,
Compatibility M20, M30) WiSER Vibe

#### **DIMENSIONS AND FIXTURE**

Dimensions 102 x 83 x51 mm
Weight 350 gr
Enclosure Material Nylamid
Fixture Standar DIN Rail (35 mm, 42 mm wide)

#### **ENVIRONMENTAL CONDITIONS**

Base Temperature Range  $-40 \,^{\circ}\text{C}$  to  $+75 \,^{\circ}\text{C}$  (-40  $^{\circ}\text{F}$  to  $+176 \,^{\circ}\text{F}$ )





## **ERBESSD INSTRUMENTS®**

### **WORLDWIDE toll-free:**

+1-877-223-4606

### **ENGLISH:**

Sales, Service & Support Engineer

+1-518-874-2700

info@erbessdreliability.com

## **SPANISH & FRENCH:**

Sales, Service & Support Engineer

+52 (55) 6280-7654 / +52 (999) 469-1603

info@erbessd-instruments.com

# BUY ONLINE www.erbessd-instruments.com